

PN 750 V Plastisolert koblingsledning i bøtte

PN 750V 2,5 G/G B1 200m

H07V-R

Nexans ref.: 10175984**El. nummer: 1060428****GTIN (EAN 13): 7045210056839**

Plastisolert koblingsledning

Beskrivelse

Isolert leder til inntrekking i rør for skjult opplegg.



Standarder

Internasjonal EN 50265; HD 21.3;
IEC 60332-1**Norsk** NEK-HD 21.3Blyfri
JaMax.conductor temp.in service
70 °CRoHS conform
JaFlammehemmende
Ja

PN 750 V Plastisolert koblingsledning i bølge

PN 750V 2,5 G/G B1 200m
Nexans ref.: 10175984

Egenskaper

Konstruksjonsegenskaper

Kapfefarge	Gul/grønn
Ledertype	Flertrådet, rund
Ledermateriale	Glødd kobber
Isolasjon	Polyvinylklorid - PVC
Blyfri	Ja

Dimensjonsegenskaper

Antall ledere	1
Antall enkelt tråder	7
Lederdiameter	2,0 mm
Ledertverrsnitt	2,5 mm ²
Vekt (ca.)	3,3 kg/100m
Nominell ytre diameter	3,6 mm

Bruksegenskaper

Lengde	200 m
Maks. tillatt ledertemperatur	70 °C
RoHS conform	Ja
Flammehemmende	Ja


Blyfri
Ja

Max. conductor temp. in service
70 °C

RoHS conform
Ja

Flammehemmende
Ja