

## PN 750 V Plastisolert koblingsledning i bøtte

PN 750V 4 Sort B1 150m

H07V-R

Nexans ref.: 10166684

El. nummer: 1060430

GTIN (EAN 13): 7045210055504

Plastisolert koblingsledning

### Beskrivelse

Isolert leder til inntrekking i rør for skjult opplegg.



### Standarder

**Internasjonal** EN 50265; HD 21.3;  
IEC 60332-1**Norsk** NEK-HD 21.3Blyfri  
JaMax. conductor temp. in service  
70 °CRoHS conform  
JaFlammehemmende  
Ja

## PN 750 V Plastisolert koblingsledning i bøtte

PN 750V 4 Sort B1 150m

 Nexans ref.: 10166684

### Egenskaper

#### Konstruksjonsegenskaper

Kappefarge	Svart
Ledertype	Flertrådet, rund
Ledermateriale	Glødd kobber
Isolasjon	Polyvinylklorid - PVC
Blyfri	Ja

#### Dimensjonsegenskaper

Antall ledere	1
Antall enkelt tråder	7
Lederdiameter	2,5 mm
Ledertverrsnitt	4 mm <sup>2</sup>
Nominell ytre diameter	4,1 mm
Vekt (ca.)	4,7 kg/100m

#### Bruksegenskaper

Lengde	150 m
Maks. tillatt ledertemperatur	70 °C
RoHS conform	Ja
Flammehemmende	Ja


 Blyfri  
 Ja

 Max. conductor temp.in service  
 70 °C

 RoHS conform  
 Ja

 Flammehemmende  
 Ja