

## PN 750 V Plastisolert koblingsledning i bøtte

PN 750V 6 Sort B1 100m

H07V-R

Nexans ref.: 10166692

El. nummer: 1060435

GTIN (EAN 13): 7045210055559

Plastisolert koblingsledning

### Beskrivelse

Isolert leder til inntrekking i rør for skjult opplegg.



### Standarder

**Internasjonal** EN 50265; HD 21.3;  
IEC 60332-1**Norsk** NEK-HD 21.3Blyfri  
JaMax. conductor temp. in service  
70 °CRoHS conform  
JaFlammehemmende  
Ja

## PN 750 V Plastisolert koblingsledning i bøtte

PN 750V 6 Sort B1 100m

 Nexans ref.: 10166692

### Egenskaper

#### Konstruksjonsegenskaper

|                |                       |
|----------------|-----------------------|
| Kappefarge     | Svart                 |
| Ledertype      | Flertrådet, rund      |
| Ledermateriale | Glødd kobber          |
| Isolasjon      | Polyvinylklorid - PVC |
| Blyfri         | Ja                    |

#### Dimensjonsegenskaper

|                        |                   |
|------------------------|-------------------|
| Antall ledere          | 1                 |
| Antall enkelt tråder   | 7                 |
| Lederdiameter          | 3,0 mm            |
| Nominell ytre diameter | 4,6 mm            |
| Ledertverrsnitt        | 6 mm <sup>2</sup> |
| Vekt (ca.)             | 6,6 kg/100m       |

#### Bruksegenskaper

|                               |       |
|-------------------------------|-------|
| Lengde                        | 100 m |
| Maks. tillatt ledertemperatur | 70 °C |
| RoHS conform                  | Ja    |
| Flammehemmende                | Ja    |


 Blyfri  
 Ja

 Max. conductor temp.in service  
 70 °C

 RoHS conform  
 Ja

 Flammehemmende  
 Ja