



ÖLFLEX® CLASSIC 110 CY

Screened PVC control cable with transparent outer sheath



Info

- CPR: Article number choice under www.lappkabel.com/cpr
- VDE reg. no. 7030
- EMC-compliant

Technical data

Classification ETIM 5/6
ETIM 5.0/6.0 Class-ID: EC000104
ETIM 5.0/6.0 Class-Description: Control cable

Core identification code
Black with white numbers acc. to VDE 0293-334

Conductor stranding
Fine wire according to VDE 0295, class 5/IEC 60228 class 5

Minimum bending radius
Occasional flexing: 20 x outer diameter
Fixed installation: 6 x outer diameter

Nominal voltage
U0/U: 300/500 V

Test voltage
4000 V

Protective conductor
G = with GN-YE protective conductor
X = without protective conductor

Temperature range
Occasional flexing: -5°C to +70°C
Fixed installation: -40°C to +80°C

Benefits

- Space-saving installation due to small cable diameters
- High electrical performance due to 4 kV test voltage

Application range

- Plant engineering
Industrial machinery
Heating and air-conditioning systems
- Conveyor and transport systems
- In EMC-sensitive environments (electromagnetic compatibility)

Product features

- Flame-retardant according IEC 60332-1-2
- Good chemical resistance, see catalogue appendix T1
- High degree of screening
low transfer impedance
(max. 250 Ω/km at 30 MHz)

Norm references / Approvals

- VDE reg. no. 7030

Product Make-up

- Fine-wire strand made of bare copper wires
- PVC insulation LAPP P8/1
- Cores twisted in layers
- PVC inner sheath, grey
- Tinned-copper braiding
- PVC outer sheath, transparent

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)	Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 110 CY									
1135752	2 X0.5	7.0	41	75	1135234	34 G1.0	20.3	505	738
1135003	3 G0.5	7.3	45.5	83	1135241	41 G1.0	22.0	578	864
1135753	3 X0.5	7.3	45.5	83	1135250	50 G1.0	23.8	688	1011
1135004	4 G0.5	7.9	55	99	1135902	2 X1.5	8.5	65	117
1135754	4 X0.5	7.9	55	99	1135303	3 G1.5	8.9	83	136
1135005	5 G0.5	8.4	66	112	1135903	3 X1.5	8.9	83	136
1135755	5 X0.5	8.4	66	112	1135304	4 G1.5	9.6	100	163
1135007	7 G0.5	8.9	80.5	132	1135904	4 X1.5	9.6	100	163
1135757	7 X0.5	8.9	80.5	132	1135305	5 G1.5	10.3	125	188
1135012	12 G0.5	11.3	138.5	202	1135905	5 X1.5	10.3	125	188
1135762	12 X0.5	11.3	138.5	202	1135307	7 G1.5	11.3	149	237
1135018	18 G0.5	13.3	156.4	289	1135907	7 X1.5	11.3	149	237
1135025	25 G0.5	15.2	250	378	1135312	12 G1.5	14.8	280	393
1135030	30 G0.5	16.1	297	429	1135318	18 G1.5	17.2	389	538
1135040	40 G0.5	18.2	343	542	1135325	25 G1.5	20.1	535	745
1135802	2 X0.75	7.4	46	86	1135334	34 G1.5	22.8	702	964
1135103	3 G0.75	7.9	57.9	100	1135341	41 G1.5	24.7	844.6	1123
1135803	3 X0.75	7.9	57.9	100	1135350	50 G1.5	27.1	1006	1372
1135104	4 G0.75	8.4	64	115	1135402	2 X2.5	9.9	112	165
1135804	4 X0.75	8.4	64	115	1135403	3 G2.5	10.3	146	192
1135105	5 G0.75	8.9	77.4	130	1135404	4 G2.5	11.3	167	233
1135805	5 X0.75	8.9	77.4	130	1135405	5 G2.5	12.6	200	283
1135107	7 G0.75	9.7	102	161	1135407	7 G2.5	13.9	288	371
1135807	7 X0.75	9.7	102	161	1135412	12 G2.5	17.6	477.3	585
1135112	12 G0.75	12.3	177	247	1135502	2 X4.0	11.4	120	247
1135812	12 X0.75	12.3	177	247	1135504	4 G4.0	13.4	237	347
1135118	18 G0.75	14.5	243	356	1135505	5 G4.0	14.7	280	413
1135818	18 X0.75	14.5	243	356	1135602	2 X6.0	13.6	180	353
1135125	25 G0.75	16.6	307.3	465	1135604	4 G6.0	15.8	318	485
1135134	34 G0.75	18.9	323.2	601	1135605	5 G6.0	17.3	441	702
1135840	40 X0.75	20.5	369.4	734	1135607	7 G6.0	18.8	530	950
1135141	41 G0.75	20.6	488	728	1135702	2 X10.0	16.4	256	492
1135852	2 X1.0	7.9	56	98	1135615	3 G10.0	17.4	362.4	507
1135203	3 G1.0	8.2	65.3	111	1135614	4 G10.0	19.0	518	735
1135853	3 X1.0	8.2	65.3	111	1135616	5 G10.0	21.3	595	847
1135204	4 G1.0	8.7	78.1	130	1135617	7 G10.0	23.2	796	1039
1135854	4 X1.0	8.7	78.1	130	1135622	2 X16.0	18.6	390	698
1135205	5 G1.0	9.5	89.4	153	1135624	4 G16.0	22.2	804	1395
1135207	7 G1.0	10.2	113.3	185	1135623	5 G16.0	24.4	935	1440
1135212	12 G1.0	13.3	188.1	307	1135626	4 G25.0	26.9	1161	1730
1135216	16 G1.0	14.6	216	390	1135627	5 G25.0	30.0	1400	2090
1135218	18 G1.0	15.5	286	418	1135625	4 G35.0	30.2	1543	2210
1135225	25 G1.0	17.5	388.5	544	1135628	5 G35.0	33.2	1901	2710

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths / Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
Photographs and graphics are not to scale and do not represent detailed images of the respective products.

ÖLFLEX® UNITRONIC® ETHERLINE® HITRONIC® EPIC® SKINTOP® SILVYN® FLEXIMARK® ACCESSORIES APPENDIX