



Product data sheet

Item No. 57.503.0055.0

Feed-through terminal WK 2,5 / U /V0

Feed-through DIN rail terminal block with screw connection for mounting on TS 35 and TS 32, nominal cross section 2.5 mm², width 5 m m, color gray



Item No.	57.503.0055.0
EAN	4015573416918
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

General

Nominal cross section	2.5 mm²
Colour	Grey
Number of levels	1
Number of clamp positions per level	2
Width/grid dimension	5 mm
Insulating housing	PA666
Inflammability class of insulation material acc. with UL94	V0
Explosion-tested version "Ex e"	Yes
Mounting method	DIN rail (top hat rail)/G-rail
Terminal blocks for electrical installations	Yes

Technical data

Rated current	24 A
Rated voltage	1000 V
Rated impulse voltage	8 kV
Pollution degree	3
Closing plate required	Yes
Type of insulation material	Thermoplastic





Length	44.5 mm	
Connection Data		
Connection type 1	Screw connection	
Connection type 2	Screw connection	
Minimum cross section solid	0.5 mm ²	
Maximum cross section solid	4 mm²	
Minimum cross section fine stranded	0.5 mm ²	
Maximum cross section fine stranded	2.5 mm ²	
Wire strip length	9 mm	
Torque conductor mounting	0.4 Nm	

Technical Data UL/CSA

Cross section UL	22-12 AWG
Voltage UL	600 V
Current factory wiring	30 A
Current field wiring	20 A
Cross section CSA	24-12 AWG
Voltage CSA	600 V
Current CSA	25 A

Technical drawing

