




## Product data sheet

Item No. 57.504.9055.0

#### Earth terminal WK 4 SL/ U /V0

Ground DIN rail terminal block with screw connection for mounting on TS 35, nominal cross section 4 mm², width 6 mm, color green/yellow



Item No.	57.504.9055.0
EAN	4015573458628
Order Unit	100 Piece(s)

# Certificates / Approvals



### Technical data

#### General

Nominal cross section	4 mm²
Colour	Green/yellow
Number of levels	1
Number of clamp positions per level	2
Width/grid dimension	6 mm
Insulating housing	PA666
Inflammability class of insulation material acc. with UL94	VO
Explosion-tested version "Ex e"	Yes
Mounting method	DIN rail (top hat rail)/G-rail
Terminal blocks for electrical installations	Yes

#### Technical data

Rated voltage	800 V
Rated impulse voltage	8 kV
Pollution degree	3
Closing plate required	No
Type of insulation material	Thermoplastic
Length	51 mm

#### Connection Data

Connection type 1	Screw connection
Connection type 2	Screw connection
Minimum cross section solid	0.5 mm <sup>2</sup>
Maximum cross section solid	6 mm <sup>2</sup>





Minimum cross section fine stranded	0.5 mm²
Maximum cross section fine stranded	4 mm <sup>2</sup>
Wire strip length	9 mm
Torque conductor mounting	0.5 Nm
Torque rail mounting	0,5

#### Technical Data UL/CSA

Cross section UL	22-10 AWG
Cross section CSA	20-10 AWG

#### Technical drawing

