

Data Sheet 1510706

Product: RS16 2L DSO 440VAC

El-number: 1510706 **Mat.no:** EKO05816 **EAN:** 7020160581617

Packing: 5

Color: Polarwhite



Product description: Double socket outlet with earth and with thermoplastic cover. Screw-socket

base. Delivered with shutters. Double sockets can be installed in single or 1,5 flush mounted boxes. It will also fit L792 housing el.nr: 14 715 65. Two

screws in the coverplate.

The socket is delivered with split socket, meaning that they can be controlled by a switch. Highly recommended if you have a lot of lamps with plugs, and

dont want to go around the house turning off the lights.

All of the cabeling must come from the same fuse. See also connection

drawings.

Technical specifications: Double split socket outlet

Voltage: 16A / 250VAC. Delivered with shutters Color: Polarwhite. Halogenfree.

Degree of protection: IP20

Screw terminals C-C distance: 60mm


Mounting: Single or 1,5 flush box, will also fit L 792 housing el.nr: 14 715 65

Depth: 19mm


Maximum torque: 1,2Nm (According to IEC 62196-1)

Maximum cross section: 4mm²

Size



Wiring diagram



ELKO AS

E-mail: elko@elko.no
Internet: www.elko.no
Bank: 6219.05.15880
Org.no.: NO 911 382 563 MVA

ELKO Front office

Sandstuveien 68, NO-0680 Oslo P.O.Box 6598 Etterstad, NO-0607 Oslo

Tel.: +47 67 80 73 00 Fax: +47 67 80 73 01 ELKO Plan

Sporpind Industriområde, NO-3340 Åmot

Tel.: +47 32 78 91 00 Fax: +47 32 78 91 01