

POWER CLEAN

Technical Data Sheet

Creation Date 28/03/2018

Version I

Mechanical parts get contaminated by the environment and by degraded lubricants. For accurate , inspection, maintenance and repair, dirt and grime should be removed.

Where to use?

Use the Power Clean on all mechanical parts contaminated with greasy or oily dirt. Clean away old lubricants before re-lubricating during maintenance or after an overhaul.

How does it work?

Power Clean is a blend of hydrocarbon solvents, known for their ability to cut through oil, grease and grime.

Liberal spray the cleaner ensuring total coverage of the contamination. Re-apply immediately, allowing the cleaner to run off from the surface, taking the grime with it. .

What to expect?

The metal surface will now be degreased, clean, and dry – ready for inspection, relubrication, or protecting.

Be prepared

- Before use, carefully read and observe the warning texts on the label
- Make sure to have a good ventilation.
- Avoid open fire or other sources of ignition in the same room.
- Dispose empty cans according to your local legislation.
- Some tissue helps to absorb excess of cleaner and dirt.

Help for a good application

- Disconnect the device from all power supplies.
- Take off protection caps if present
- Shield the environment of the area to clean.
- Shake the can during 1 minute.
- Spray on the area to clean with a short blast.
- Repeat the spraying as soon as the part gets dry.
- Allow the product to run off on a light coloured tissue.
- Observe the product running off. It will be completely transparent when the part is clean.
- Allow the cleaned part to dry completely.
- In case of necessity, protect cleaned metal parts with CRC 5-56 against corrosion.

Technical data (Aerosol)

Colour:	Clear liquid
Odour:	Typical
Evaporation:	Fast
Compatibility:	Ok for metals and technical plastics
Volume	: 250 ML



Related products:

- CRC 5-56
- CRC Lubricants range

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

