ARGENTA INOX SERIES

IP66 STAINLESS STEEL WALL-MOUNTING CABINETS

Description: IP66 INOX WALL-MOUNTING CABINET 800x600x300 316L   **Reference:** INX806030-316

Characteristics:

Product type:	316L Stainless steel wall-mounting cabinet
Dimensions cabinet:	(AxBxC) 800x600x300 mm
Installation:	Surface
Type of door:	Single opaque door
Locking:	5-mm double-bit zamak lock - Two 1-point lock
Finish:	Scotch 320 satin finish.
Colour:	-
Mounting plate:	With flat mounting plate. 2-mm galvanised sheet steel
Weight (Kg):	32,8
Materials:	AISI 316L stainless steel.
	Injected polyurethane sealing gasket.

Technical data:

Degree of protection:	IP66 / NEMA 1, 12, 4x
Resistance to impact:	IK10
Ambient temperature range:	-25 ºC / +40 ºC
Maximum operating voltage:	1000 V AC
Corrosion resistance:	-

Certificates and standards:

|	
Directive:	2014/35/EU
Standards:	UNE-EN 62208 / UNE-EN 61439-1 (as applicable).
Certificates:	UL508A

CE   c(UL)us LISTED

ARGENTA INOX SERIES

IP66 STAINLESS STEEL WALL-MOUNTING CABINETS

Description: IP66 INOX WALL-MOUNTING CABINET 800X600X300 316L

Reference: INX806030-316

Pictures and drawings are standards. To get more details please surf www.ide.es to download those files (pdf, dxf, igs).

Dimensions cabinet:	(AxBxC) 800x600x300 mm	Cable entry:	-
Body to be flush-fitted:	-	Wall fixing:	(Height x Width) 760x560 mm
Inside usable space:	(Height x Width x Depth) 750x550x279 mm		

Sustainability:

RoHS - REACH

Supply:

Supplied in individual packaging containing cabinet, plate and accessory bag. The cabinet is protected by a plastic bag. Mounting plate is supplied assembled inside the cabinet.

Product end of life:

It does not require specific recycling operations.

Recommended applications

Industrial environments and outdoor facilities with aggressive agents or saline environments, food, chemical and petrochemical industries, where a high degree of hygiene is required. Sea ports and areas with a high salt or chlorine concentration.