

Cat.6 Flush Mount Wall Plate 2 ports



Materials Specifications

Plastic Body : Fireproof ABS UL-94V0
RJ-45 Jack : Housing-PBT/

UTP 8P8C 50 micro inches gold plated
PCB : FR-4 / 1.6mm UL-94V0

IDC Body : Fireproof ABS UL-94V0
IDC Pin : Bronze & Tinned

Color Code : T568 A/B

IDC Description : For 22-26 AWG / For 110 or LSA+ punch-down Tool
Length : 84mm **Depth** : 84mm **Height** : 27mm

Electrical Specifications

Insulation Resistance : 500M ohms (min.)
Contact Resistance : 20m ohms (max.)

Current Rating : 1.5 Amps .

DC Resistance : 0.1 ohm (max.)

Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

Mechanical Specifications

IDC Punch Down Cycle : Over 25 Cycles (min.)

RJ-45 Jack Insertion Cycle : Over 2000 Cycles (min.)

Operation Temperature : -40 ~ +70 degree / C

ITEM No	Description
---------	-------------

NOR-P2-C6 30601002	Cat.6 Flush Mount Wall Plate 2 ports
-----------------------	--------------------------------------

DGROUP A/S

PO.Box 2409

3103 Tonsberg-Norway

Tel:+47 33 32 94 30

Fax:+47 33 32 99 45

post@dgroup.no

www.dgroup.no