

Quadrat 230V



230V, 50-60Hz, Class II, IP23*, GU10, Max 35W

	h (min.)	
Quadrat 35W	150mm	1xØ120mm
Quadrat 2x35W	150mm	2xØ120mm
Quadrat 3x35W	200mm	3xØ120mm
Quadrat 7W LED	150mm	1xØ120mm
Quadrat 2x7W LED	150mm	2xØ120mm
Quadrat 3x7W LED	200mm	3xØ120mm

35W Halogen:

7W LED:

NO: Minimumsavstand til brennbar materiale i armaturens stråleretning.
 EN: Minimum distance to flammable material in the beam direction.
 FR: Distance minimum entre le faisceau lumineux de l'armature et toute matière inflammable.
 NL: Minimale afstand tussen de lichtstraal van de armatuur en het brandbaar materiaal.
 DE: Der kleinste Abstand zum brennbaren Material in die Richtung des Lichtstrahls.

Halopar 16,
240V, 35W, 35°

ca 10° (max. 20°)
Max 16A

Philips Master LED MV
Reflector, 7W, GU10,
230-240V, 25°, 1000cd,
50-60Hz, typ. 45mA

SG Downlightbox

SG Sealbox & Frame

Rev. 16.05.2011

SG Armaturen AS
Svaabekk Industriområde
N-4790 Lillesand
NORGE
Tel: +47 37 26 84 84
www.sg-as.no

SG Armaturen AB
August Barksg. 30B
SE-421 32 Västra Frölunda
SVERIGE
Tel: +46 31 81 71 10
www.sg-ab.se

SG Lighting SA/NV
Wayenborgstraat 4
B-2800 Mechelen Noord II
BELGIQUE/BELGIË
Tel: +32 (0) 15 20 72 71
www.sglighting.net

SG Lighting SA/NV
Parc de l'Arboretum
73 rue de Saint Mandrier
83140 Six Fours Les Plages
FRANCE
Tel: +33 04 94 93 00 00
www.sglighting.net

SG Leuchten GmbH
Nordstrasse 53
D-59399 Olfen
DEUTSCHLAND
Tel: 0152-57000500
www.sg-leuchten.de