

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: J&EL

Supplier's address: Namron AS, Address: Nedre kalbakkvei 88B, 1081, Oslo, Norway

Model identifier: 3222259

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Terminal		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	6	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	520 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700 or 3 200 or 4 000
On-mode power (P_{on}), expressed in W	6,5	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,50
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without	Height	Spectral power distribution in the	See image in last page
	Width		
	Depth		

separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	6	
		Chromaticity coordinates (x and y)	0,450 0,400	
Parameters for directional light sources:				
Peak luminous intensity (cd)	801	Beam angle in degrees, or the range of beam angles that can be set	38	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	67	Survival factor	0,90	
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ 1)	0,50	Colour consistency in McAdam ellipses	3	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,8	Stroboscopic effect metric (SVM)	0,1	

(a) : not applicable;

(b) : not applicable;

Spectrum Test Report

Sample : 0
Specification : 3222259
Sample No. : 1
Manufacturer : EVERFINE


Date : 2021-01-17 17:31:17
Sam. Status :
Instrument : HAAS-2000(EVERFINE)
Test by : DAMIN
Assessor : damin

Test Condition

Temperature : 85Deg
WL Range : 350nm-1000nm
Test Mode : Fast Test

RH : 65.0%
IP : 52178 (80%)
T : 466 ms
Sensitivity : High

Spectrum



Colorimetric Parameters

Chromaticity Coordinate: $x = 0.4589$ $y = 0.4073$ / $u' = 0.2634$ $v' = 0.5259$ ($duv = -1.15e-03$) $Dx, Dy: -0.0020, -0.0036$

CCT= 2688K Prcp WL: $L_d = 584.7$ nm Purity=60.0%

Peak WL: $L_p = 623$ nm FWHM: =142.6nm Ratio:R=27.0% G=70.4% B=2.6%

Render Index: $R_a = 95.0$ AvgR = 93.2 TM30:Rf=93 Rg=101

R1 =96 R2 =99 R3 =99 R4 =96 R5 =96 R6 =97 R7 =92

R8 =84 R9 =67 R10=96 R11=98 R12=89 R13=97 R14=99 R15=92

LEVEL:OUT WHITE:ANSI_2700K

Photometric & Radiometric Parameters

Flux = 597.63 lm Eff. : 83.87 lm/W $F_e = 2.1519$ W

(EQE):2989.5%

Flux of emitted photons($\mu\text{mol/s}$):10.693 Fluo. and blue light ratio:14.78 Fluorescent eff.:250.7

B: $2.1519e+003$ mW

Electrical parameters

V = 230.7 V I = 0.03486 A P = 7.126 W PF = 0.8861

Kdisp(IEC) = 0 Freq=49.99 Hz