

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Namron

**Supplier's address:** Namron AS, Nedre kalbakkvei 88B, 1081, Oslo, Norway

**Model identifier:** 3222261

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Terminal		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

## Product parameters

Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	3	Energy efficiency class	G
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	300 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power ( $P_{on}$ ), expressed in W	3,0	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,50
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	98
Outer dimensions without separate control gear, lighting control	Height	15	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	70	
	Depth	70	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,459 0,413
<b>Parameters for directional light sources:</b>			
Peak luminous intensity (cd)	567	Beam angle in degrees, or the range of beam angles that can be set	38
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	92	Survival factor	0,90
the lumen maintenance factor	0,96		

(a): not applicable;

(b): not applicable;

## Spectrum Test Report

Sample :  
Specification : 3222261  
Sample No. : 5  
Manufacturer : EVERFINE


Date : 2020-06-18 19:33:03  
Sam. Status :  
Instrument : HAAS-2000(EVERFINE)  
Test by : DAMIN  
Assessor : damin

### Test Condition

Temperature : 25Deg  
WL Range : 350nm-1000nm  
Test Mode : Fast Test

RH : 65.0%  
IP : 50862 (78%)  
T : 1045 ms  
Sensitivity : High

### Spectrum



### Colorimetric Parameters

Chromaticity Coordinate:  $x = 0.4597$   $y = 0.4134$  /  $u' = 0.2611$   $v' = 0.5284$  ( $duv=1.05e-03$ )  $Dx, Dy: 0.0018, 0.0033$

CCT= 2725K Prcp WL:  $L_d=583.8nm$  Purity=62.1%

Peak WL:  $L_p=637nm$  FWHM: =154.0nm Ratio:R=27.0% G=70.4% B=2.6%

Render Index:  $R_a = 98.4$   $AvgR = 97.1$

R1 =99 R2 =100 R3 =97 R4 =98 R5 =100 R6 =98 R7 =99

R8 =97 R9 =92 R10=98 R11=96 R12=90 R13=99 R14=97 R15=98

LEVEL:OUT WHITE:ANSI\_2700K

### Photometric & Radiometric Parameters

Flux = 303.69 lm Eff. : 46.81 lm/W  $F_e = 1.1774 W$

(EQE):1229.6%

Flux of emitted photons( $\mu mol/s$ ):5.9057 Fluo. and blue light ratio:16.29 Fluorescent eff.:102.4


B:  $1.1774e+003mW$

### Electrical parameters

$V = 230.8 V$   $I = 0.04694 A$   $P = 6.488 W$   $PF = 0.5987$

$K_{disp}(IEC) = 0$  Freq=49.89 Hz

Model placed on the Union market from 01/09/2021



**EPREL registration number:** 799358

<https://eprel.ec.europa.eu/qr/799358>

**Supplier:** NAMRON AS (Importer)

**Website:** [www.namron.com](http://www.namron.com)

**Customer care service:**

**Name:** Namron AS

**Website:** [www.namron.com](http://www.namron.com)

**Email:** [post@namron.com](mailto:post@namron.com)

**Phone:** +47 2281 2770

**Address:**

Nedre kalbakkvei 88B, 1081, Oslo, Norway