

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Namron

Supplier's address: Namron AS, Nedre kalbakkvei 88B, 1081 Oslo, NO

Model identifier: 3306777

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Other electric interface		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	15	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 610 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P_{on}), expressed in W	15,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,440 0,403	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	0	Survival factor	0,90	
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,70	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4	

(a) '-': not applicable;

(b) '-': not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.4365$ $y=0.4023$ $u'=0.2511$ $v'=0.5206$
 CCT=2993K(Duv=-0.0007) Dominant WL:Ld =583.1nm WL:Lc = --nm Purity=51.8%
 Ratio:R=22.8% G=74.7% B=2.5% Peak WL:Lp=604.0nm FWHM=119.8nm
 Render Index:Ra=81.1 AvgR=75.1

R1 =79 R2 =90 R3 =96 R4 =79 R5 =80 R6 =88 R7 =81
 R8 =56 R9 =-1 R10=78 R11=78 R12=71 R13=82 R14=98 R15=71

Photo Parameters:

Flux = 1614 lm Eff. : 108.08 lm/W Fe = 4.861 W

Electrical parameters:

V = 229.89 V I = 0.07015 A P = 14.93 W PF = 0.9258


Kdisp(IEC) = 0.9468

LEVEL:OUT WHITE:ANSI_3000K

Status: Integral T = 36 ms Ip = 48234 (74%)

GBT5702

Model placed on the Union market from 10/10/2021



EPREL registration number: 855240

<https://eprel.ec.europa.eu/qr/855240>

Supplier: NAMRON AS (Importer)

Website: www.namron.com

Customer care service:

Name: Namron AS

Website:

Email: post@namron.com

Phone: +4722812770

Address:

Nedre kalbakkvei 88B

1081

Norway