

Tech Specs

What's in the box

Sensibo WiFi controller for air conditioners and heat pumps & air quality monitor

Power adapter

Double-sided adhesive



Compatibility

Any air conditioner with a remote control

Any heat pump with a remote control

Supported types of air conditioners:

- ✔ Window
- ✔ Split
- ✔ Cassette
- ✔ Portable
- ✔ Central

Powering method

5V 1A micro USB adapter

Operating voltage - 110-240V

Connectivity and security

2 radios - WiFi, Bluetooth Low Energy (BLE)

WiFi 802.11 b/g/n @ 2.4GHz

DHCP or static IP addressing

SSL encryption

Bandwidth

15-20 MB/month

Sensors

TVOC (Total Volatile Organic Compound)

CO2 equivalent (using TVOC)

Temperature

Humidity

2 Infrared receivers

Green

Recyclable packaging

Mercury-free

Arsenic-free

PVC free

RoHS compliant

Temperature range

Operating: 0° to 55°C (32° to 130°F)

Sensitivity: ±0.5°C (±1°F)

Humidity range

Range: 5% to 95% RH

Sensitivity: ±5% RH

Product dimensions

Depth: 17mm (0.67")

Width: 65mm (2.56")

Height: 65mm (2.56")

Apps

iOS

Android

Web (HTML5)

Voice Assistants

Amazon Echo (Alexa)

Google Home

Apple HomeKit

SmartThings

IFTTT

Open API

App Languages

Available in over 10 languages

Warranty

1-year warranty

Learn more at sensibo.com
support@sensibo.com