



Designation IEC:

HR 03

Size:..... AAA
 Nominal Voltage:..... 1.2 V
 Rated Capacity:..... 1000 mAh
 Internal Resistance DC, fully charged:..... 80 mOhm
 Impedance AC at 1kHz, fully charged:..... 40 mOhm

Typical Capacity at:

0.2 C / 1.00 V:..... 1000 mAh
 1.0 C / 0.90 V:..... 850 mAh
 Max Discharge Current (continuous / 0.8 V):..... 2.0 A

Charge Retention:

After one year 65% of initial capacity at 20° C determined at 0.2 C rate

Dimensions (including shrink sleeve/label):

Diameter a:..... 10.5 ^{-1.0} mm
 Height b:..... 44.5 ^{-1.2} mm
 Shoulder Height c:..... 43.7 ^{-1.2} mm
 Cap Diameter d:..... 3.8 ^{-2.0} mm
 Volume:..... 3.8 cm³
 Weight approx:..... 14 g

Charge Conditions at:

Standard Charge:..... 100 mA, 16 h
 Fast Charge:..... 1000 mA (dT/dt, -dV)
 Trickle Charge (0.03 - 0.05 C):..... 30 – 50 mA

Temperatures (recommended / permissible) at:

Storage:..... -20° C ... 25° C / -20° C ... 40° C
 Charge:..... 15° C ... 30° C / 0° C ... 45° C
 Fast Charge:..... 15° C ... 30° C / 0° C ... 40° C
 Discharge:..... 0° C ... 40° C / 0° C ... 50° C

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries