



Type Designation	4903
Designation IEC	LR03
System	Zn-MnO ₂ (Alkaline)
Shelf Life (Coding)*	10 years
Nominal Voltage [V]	1.5
Typical Capacity C [mAh]	1250 (discharge with high-resistance)
Permissible Temperature Range	- 10 °C ... 50 °C
Weight, approx. [g]	11
Volume [ccm]	3.8

Dimensions [mm] min: max:

Ø	9.5	10.5
A	-	44.5
B	43.3	-
C	4.3	-
E	-	0.5
F	-	3.8
G	0.8	-

Typical Capacities (at 20°C):



Discharge Type	Load	End Voltage[V]	0.9
4M/H, 8H/D, 7D/W	5.1 Ω	Time [min]	262
Portable lighting		Capacity [mAh]	1009
		Energy [mWh]	1200
Discharge Type	Load	End Voltage[V]	0.8
1H/D, 7D/W	5.1 Ω	Time [h]	4,6
Toy		Capacity [mAh]	998
		Energy [mWh]	1115
Discharge Type	Load	End Voltage[V]	1.0
15S/M, 8H/D, 7D/W	24 Ω	Time [h]	21,1
Remote control		Capacity [mAh]	1108
		Energy [mWh]	1408
Discharge Type	Load	End Voltage[V]	0.9
4H/D, 7D/W	75 Ω	Time [h]	73,1
Radio		Capacity [mAh]	1230
		Energy [mWh]	1548

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries

* In consideration of typical loss of capacity at storage and application.