

<b>PV Input Data</b>	<b>BNT003KTL</b>	<b>BNT004KTL</b>	<b>BNT005KTL</b>	<b>BNT006KTL</b>	<b>BNT008KTL</b>	<b>BNT010KTL</b>
Max. DC Power ( W )	5100	6000	7500	9000	12000	15000
Max. DC Voltage ( V )	1100					
MPPT Voltage Range ( V )	150 - 1000					
MPPT Full Power Voltage Range ( V )	200 - 850		250 - 850		300 - 850	500 - 850
Rated Input Voltage ( V )	620					
Start-up Voltage ( V )	150					
Max. Input Current ( A )	15 x 2					
Max. Short Current ( A )	25 x 2					
No. of MPP Tracker / No. of PV String	2/2					
Input Connector Type	MC4					
<b>AC Output Data</b>	<b>BNT003KTL</b>	<b>BNT004KTL</b>	<b>BNT005KTL</b>	<b>BNT006KTL</b>	<b>BNT008KTL</b>	<b>BNT010KTL</b>
Max. Output Power ( W )	3300	4400	5500	6600	8800	11000
Nominal Output Power ( W )	3000	4000	5000	6000	8000	10000
Max. Output Current ( A )	5.3	7	8.5	10.5	13.5	17
Nominal Output Voltage ( V )	3P+N+PE /3P+PE 230/400					
Grid Voltage Range	260Vac-519Vac (according to local standard)					
Nominal Output Frequency ( Hz )	50/60					
Grid Frequency Range	45-55Hz/55-65Hz(according to local standard)					
Output Power Factor	1 default (adjustable from 0.8 leading to 0.8 lagging)					
Output Current THD	<3%					
<b>Efficiency</b>	<b>BNT003KTL</b>	<b>BNT004KTL</b>	<b>BNT005KTL</b>	<b>BNT006KTL</b>	<b>BNT008KTL</b>	<b>BNT010KTL</b>
Max. Efficiency	98.30%					98.70%
Euro Efficiency	97.61%	97.65%	98.00%	98.05%		98.23%
<b>Protection</b>	<b>BNT003KTL</b>	<b>BNT004KTL</b>	<b>BNT005KTL</b>	<b>BNT006KTL</b>	<b>BNT008KTL</b>	<b>BNT010KTL</b>
PV Reverse Polarity Protection	YES					
PV Insulation Resistance Detection	YES					
AC Short Circuit Protection	YES					
AC Over Current Protection	YES					
AC Over Voltage Protection	YES					
Anti-Islanding Protection	YES					
Residual Current Detection	YES					
Over Temperature Protection	YES					
Integrated DC switch	YES					
Surge Protection	Integrated (Type II)					
Smart IV Curve Scanning	YES					
Quick Arc Fault Circuit Interruption	Optional					
<b>General Data</b>	<b>BNT003KTL</b>	<b>BNT004KTL</b>	<b>BNT005KTL</b>	<b>BNT006KTL</b>	<b>BNT008KTL</b>	<b>BNT010KTL</b>
Dimensions (H x W x D, mm)	510 x 370 x 167			510 x 370 x 192		
Weight ( kg )	16				15	
Protection Degree	IP65					
Enclosure Material	Aluminum					
Ambient Temperature Range (°C)	-25 to 60					
Humidity Range	0-100%					
Topology	Transformerless					
Communication Interface	RS485 / WiFi / Wire Ethernet / GPRS (optional)					
Cooling Concept	Convection				Intelligent fan cooling	
Noise Emission ( db )	<30					
Night Power Consumption ( W )	<1					
Max. Operation Altitude ( m )	≤4000					
<b>Certifications and Standards</b>	<b>BNT003KTL</b>	<b>BNT004KTL</b>	<b>BNT005KTL</b>	<b>BNT006KTL</b>	<b>BNT008KTL</b>	<b>BNT010KTL</b>
EMC Standard	EN/IEC 61000-6-2, EN/IEC 61000-6-3, EN61000-3-2, EN61000-3-3, EN61000-3-11, EN61000-3-12					
Safety Standard	IEC 60068, UL1741, EN62109					
Grid-connection	IEEE1547, CSA C22, EN50549, VDE4105, VDE0126, RD1699, ABNT NBR16149 & 16150, AS4777.2, NB/T32004, G98/G99, IEC61727					