

Three Phase PV String Inverter

30-60 kW



The Afore BNT Series Three-phase string inverters are designed for commercial and power plant PV system applications, rating from 30kW to 60kW. All models with aluminum housing which is anodized, increasing durability and effectively prevents corrosion. Equipped with external inductors, ensure efficient heat dissipation, which significantly improves the reliability and extends the life of the inverters.

The inverter menu is activated by sensor touch buttons. Communication implements are via the Wi-Fi module (which can be changed to Ethernet / GPRS). Check the system status anytime and anywhere via online portal or APP.

Max. 20A	Max. 1.5					
MAX. 20Adc String Current Up To 20A	PV OVERTIME Max. 1.5 Time PV Oversize Input	PROTECTION Multiple Intelligent Protections	ANTI-FLOW Anti-Feed-in Function	WI-FI Wi-Fi Standard, Ethernet/GPRS Optional	CONFIGURATION Quick & Easy Config. via Wi-Fi	MODBUS MODBUS Communication Ready

- MPPT efficiency > 99.9%
- Intelligent Temperature Control System
- Active and reactive power compensation, adjust power factor
- IP 68 Cooling Fan
- Type II DC & AC lightning protection
- AC output 1.1x continuous operation

Technical Data	BNT030KTL	BNT036KTL	BNT040KTL	BNT050KTL	BNT060KTL
PV Input Data					
Max. DC Power (W)	45000	54000	60000	75000	90000
Max. DC Voltage (V)		1100			
MPPT Voltage Range (V)			200-1000		
MPPT Full Power Voltage Range (V)			500-850		
Rated Input Voltage (V)			620		
Start-up Voltage (V)			200		
Max. Input Current (A)	38x2		38x3	40x3	38x4
Max. Short Current (A)	48x2		48x3	48x3	48x4
No. of MPP Tracker / No. of PV String	2/5		3/6	3/7	4/8
Input Connector Type				MC4	
AC Output Data					
Max. Output Power (VA)	33000*	39600*	44000*	55000*	66000*
Nominal Output Power (W)	30000	36000	40000	50000	60000
Max. Output Current (A)	48	60	65	80	96
Nominal Output Voltage (V)			3P+N+PE /3P+PE 230/400		
Grid Voltage Range			260Vac-519Vac (according to local standard)		
Nominal Frequency (Hz)			50/60		
Grid Frequency Range			45-55Hz/55-65Hz (according to local standard)		
Output Power Factor			1 default (adjustable from 0.8 leading to 0.8 lagging)		
Output Current THD			<3%		
Efficiency					
Max. Efficiency	98.50%	98.65%	98.65%	98.80%	99.00%
Euro Efficiency	98.10%	98.20%	98.25%	98.45%	98.50%
Protection					
PV Reverse Polarity Protection			YES		
PV Insulation Resistance Detection			YES		
AC Short Circuit Protection			YES		
AC Over Current Protection			YES		
AC Over Voltage Protection			YES		
Anti-Islanding Protection			YES		
Residual Current Detection			YES		
Over Temperature Protection			YES		
Integrated DC switch			YES		
Surge Protection			Integrated (Type II)		
Smart IV Curve Scanning			YES		
Quick Arc Fault Circuit Interruption			Optional		
General Data					
Dimensions (W x H x D, mm)	450x485x210			710x470x236	
Weight (kg)	26		44		51
Protection Degree			IP65		
Enclosure Material			Aluminum		
Ambient Temperature Range (°C)			-25 to 60		
Humidity Range			0-100%		
Topology			Transformerless		
Communication Interface			RS485 / WiFi / Wire Ethernet / GPRS (optional)		
Cooling Concept			Intelligent Fan Cooling		
Noise Emission (dB)	-51			<55	
Night Power Consumption (W)			<1		
Max. Operation Altitude (m)			≤4000		
Certifications and Standards					
EMC Standard	EN/IEC 61000-6-2, EN/IEC 61000-6-5, EN61000-3-2, EN61000-3-3, EN61000-3-11, EN61000-3-12				
Safety Standard			IEC 60068, UL1741, EN62109		
Grid connection			IEEE1547, CSA C22, EN50549, VDE4105, VDE0126, RD1699, ABNT NBR16149 & 16150, AS4777.2, NB/T32004, G98/G99, IEC61722		

* For Max. Output Power (VA) BNT030KTL is 30000; BNT036KTL is 36000; BNT040KTL is 40000; BNT050KTL is 50000; BNT060KTL is 60000.