



Data Sheet 6630098

Product: RS16 USB lader 2,1A I PH
El-number: 6630098
Mat.no: EKO05982
EAN: 7020160598219
Packing: 1
Color:



Product description: USB charger for electronic equipment, cellphones, mp3 players and tablets. Charging capacity 2100mA, 5V
Fits in to ELKO Plus or RS16 combination plates.
Connected to 230V, integrated fuse with auto reset.


Technical specifications: Voltage: 100-240 V/50 Hz. +/-10%
USB output voltage: 5V DC +/-5%
Nominal output current: 2,1A in one output, 1,05A if both of the outputs are used
Power consumption stand by: < 0,1W
Maximum output power: 10,5W
Overvoltage category: OVC III
Isolation class: Class II

Protection of short circuit on the connected charging cable. Auto reset when the damaged cable is removed.


Stripping length: 7mm
Maximum torque: 0,33Nm
Maximum cross section: 2 x 2,5mm² pr. terminal

Surface housing: 33mm.
IP20
Depth in box: 27mm

Size



Wiring diagram



ELKO AS

E-mail: elko@elko.no
Internet: www.elko.no
Bank: 6219.05.15880
Org.no.: NO 911 382 563 MVA

ELKO Front office
Sandstuveien 68, NO-0680 Oslo
P.O.Box 6598 Etterstad, NO-0607 Oslo
Tel.: +47 67 80 73 00
Fax: +47 67 80 73 01

ELKO Plant
Sporpind Industriområde, NO-3340 Åmot
Tel.: +47 32 78 91 00
Fax: +47 32 78 91 01