

LANmark Patchpaneler for Snap-in konnektorer

Patchpanel 24 Snap-in Fast skuff Sort

Kontakt

Nexans Cabling Solutions
firmapost@nexans.com

Nexans ref.: [N521.661BK](#)

El. nummer: 6950815

- Kompatibel med alle Snap-In kontakter
- 24 Snap-In-porter med støvdeksler
- Clip-on mekanisme
- Eksklusivt Auto-Connect jordingssystem
- Universell design som støtter uskjærmede og skjærmede konnektorer
- Finnes også i hvit

BESKRIVELSE

Nexans Snap-In range of patch panels are designed to accommodate any of the Snap-In connectors in the LANmark product family (LANmark-7A, LANmark-7, LANmark-6A, LANmark-6, and LANmark-5).

The Snap-In panels feature an exclusive Clip-On system to secure the connector in the panel and to provide a simple means of earthing shielded connectors to facilitate installation. Connection of the panel to earth is achieved with a unique Auto-Connect feature removing the need for individual bonding conductors.

The panels also have a series of complementary cable management products such as blank panels and patch cord guides.

The patch panels are designed for standard 19" enclosures, are 1U high, and support the following common features:

- 24 Ports with shutters
- Designed for Screened and Unscreened Snap-In connectors
- Compatible with all performance categories of connector
- Clip-On mechanism for simple earthing
- Exclusive rear cable management facilities
- Robust construction
- Printed numbering for port labelling

This panel features vertical "T" clips for rapid cable retention which allows loading of the panel in around 25% of the time needed to fasten tie wraps which leads to time saving during installation.



LANmark

STANDARDER

Internasjonal ISO/IEC 11801

LANmark Patchpaneler for Snap-in konnektorer

Patchpanel 24 Snap-in Fast skuff Sort

Kontakt

Nexans Cabling Solutions
firmapost@nexans.com

EGENSKAPER

Konstruksjonsegenskaper

Farge	Svart
Materiale	Steel

Dimensjonsegenskaper

Høyde	1 U
Dybde	75 mm
Vekt pr. stk. (ca.)	0,65 kg
Bredde	19 in

Bruksegenskaper

Bruksområde	Faste installasjoner
Motstand mot vibrasjon	Høy
Mechanical Resistance	Good mechanical resistance
Antall porter	24
Forpakning	Eske