

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Namron

**Supplier's address:** Namron AS, Nedre kalbakkvei 88B, 1081 Oslo, NO

**Model identifier:** 3306777

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Other electric interface		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## Product parameters


Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	15	Energy efficiency class	F
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 610 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power ( $P_{on}$ ), expressed in W	15,0	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	2	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	156	
	Depth	156	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,440 0,403
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	0	Survival factor	0,90
the lumen maintenance factor	0,96		
<b>Parameters for LED and OLED mains light sources:</b>			
displacement factor (cos $\phi_1$ )	0,70	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a)-: not applicable;

(b)-: not applicable;

## Spectrum Test Report



## Color Parameters:

Chromaticity Coordinate:  $x=0.4365$   $y=0.4023$   $u'=0.2511$   $v'=0.5206$   
 CCT=2993K (Duv=-0.0007) Dominant WL:Ld =593.1nm WL:Lc = --nm Purity=51.8%  
 Ratio:R=22.8% G=74.7% B=2.5% Peak WL:Lp=604.0nm FWHM=119.8nm  
 Render Index:Ra=81.1 AvgR=75.1

R1 =79 R2 =90 R3 =96 R4 =79 R5 =80 R6 =88 R7 =81  
 R8 =56 R9 =-1 R10=78 R11=78 R12=71 R13=82 R14=98 R15=71

## Photo Parameters:

Flux = 1614 lm Eff. : 108.08 lm/W Fe = 4.861 W

## Electrical parameters:

V = 229.89 V I = 0.07015 A P = 14.93 W PF = 0.9258


Kdisp(IEC) = 0.9468

LEVEL:OUT WHITE:ANSI\_3000K

Status: Integral T = 36 ms Ip = 48234 (74%)

GBT5702

Model placed on the Union market from 10/10/2021



**EPREL registration number:** 855240

<https://eprel.ec.europa.eu/qr/855240>

**Supplier:** NAMRON AS (Importer)

**Website:** [www.namron.com](http://www.namron.com)

**Customer care service:**

**Name:** Namron AS

**Website:**

**Email:** [post@namron.com](mailto:post@namron.com)

**Phone:** +4722812770

**Address:**

Nedre kalbakkvei 88B

1081

Norway