

PN 750 V Plastisolert koblingsledning i bøtte

PN 750V 6 Brun B1 100m

H07V-R

Nexans ref.: 10166696

El. nummer: 1060439

GTIN (EAN 13): 7045210055597

Plastisolert koblingsledning

Beskrivelse

Isolert leder til inntrekking i rør for skjult opplegg.



Standarder

Internasjonal EN 50265; HD 21.3;
IEC 60332-1**Norsk** NEK-HD 21.3Blyfri
JaMax. conductor temp. in service
70 °CRoHS conform
JaFlammehemmende
Ja

PN 750 V Plastisolert koblingsledning i bøtte

PN 750V 6 Brun B1 100m

 Nexans ref.: 10166696

Egenskaper

Konstruksjonsegenskaper	
Kappefarge	Brun
Ledertype	Flertrådet, rund
Ledermateriale	Glødd kobber
Isolasjon	Polyvinylklorid - PVC
Blyfri	Ja
Dimensjonsegenskaper	
Antall ledere	1
Antall enkelt tråder	7
Lederdiameter	3,0 mm
Nominell ytre diameter	4,6 mm
Ledertverrsnitt	6 mm ²
Vekt (ca.)	6,6 kg/100m
Bruksegenskaper	
Lengde	100 m
Maks. tillatt ledertemperatur	70 °C
RoHS conform	Ja
Flammehemmende	Ja


 Blyfri
 Ja

 Max. conductor temp.in service
 70 °C

 RoHS conform
 Ja

 Flammehemmende
 Ja